



Mirror cabinet	Dimension	Weight	Order number
cEGS/IAPMO®*, 2 mirror doors, 2 glass shelves, 1 sensor switch bottom right, LED (life span > 30,000 hours), LED dimming function, LED module permanently enclosed, GFCI outlets are not supplied by the manufacturer (GFCI outlets can be added to the cabinet by a certified electrician on the job site), mirror cabinets require a GFCI 110 V 60 Hz power source, flat plug will be supplied with the mirror cabinet, LED module 3500 kelvin light color, 20 Watt			
Colors			
M07 Concrete Gray Matt Decor M09 Light Blue Matt Decor M18 White Matt M21 Walnut Dark Decor M22 White High Gloss (Decor) M31 Pine Silver (Decor) M43 Basalt Matt (Decor) M49 Graphite Matt (Decor) M51 Pine Terra (Decor) M52 European Oak (Decor) M53 Chestnut Dark (Decor) M73 Ticino Cherry Tree (Decor) M75 Linen (Decor) M79 Natural Walnut (Decor) M91 Taupe Matt (Decor)			
Variant			
	39 3/8" x 7 1/8" In	ch	KT7532
Infobox			
* Complies with following standards: UL 962 and CSA C22.2 No. surfaces = minimum 3"	12-1982, Distance b	etween sensor and reflecting	
Suitable products			
Magnetic strip in stainless steel , 3 1/2" Inch	3 1/2" Inch		UV9709

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.