



| 12 | Logo 2.0 gpm DOE cUPC | 1 | - | 09 0093 | - |
|------|---------------------------------|------|----------------------|-------------------|---------------|
| 11 | Logo In2Aqua | 1 | - | 09 0114 | - |
| 10 | Disk Clean-Air PURE 140 | 1 | ABS | 01 0621 | JA180305 |
| 9 | ORing \varnothing 126.72x1.78 | 1 | EPDM 70 SHA | 02 0007-050 | J99980123 |
| 8 | Clean Gasket PURE 140 | 1 | SILICON | 02 0158 | JA185000 |
| 7 | Conveyer PURE 140 welded | 1 | PPE+PS | 04 0051 | JA180200 |
| 6 | Body headshower PURE 140 | 1 | ABS | 01 0590 | VA320105/01 |
| 5 | ORing \varnothing 18x3 | 1 | NBR | 02 0007-001 | 99980027 |
| 4 | Ball Joint 1/2" NPT | 1 | BRASS | 03 0078 | V125405NPT |
| 3 | Flow limiter 2.0 gpm | 1 | VARIED | 80 0137 | J26550164/2.0 |
| 2 | Ring | 1 | POM | 01 0141 | V1251NPT |
| 1 | Crown | 1 | BRASS | 03 0301 | VA370305 |
| Pos. | DENOMINAZIONE / DESCRIPTION | Q.ty | MATERIALE / MATERIAL | DISEGNO / DRAWING | CODICE / CODE |

Note: Please apply thread seal tape (also known as plumber's tape) to all threads

Ingrassare O-ring con grasso tipo BESSIL BESLUX EH-000
Put grease type BESSIL BESLUX EH-000 on the O-ring

in2aqua

in2aqua GmbH

Königstrasse 26 • 70173 Stuttgart, Germany
Phone: +49 (0)7127 9296 141 • 1 800 257 6051
www.in2aqua.de • www.in2aqua.com • info@in2aqua.com